



IAC PRIME -516K
CASHLESS

قابلیت‌ها:

- انجام کلیه تراکنش‌های تعریف شده بر روی دستگاه خودپرداز (به غیر از دریافت وجه نقد)
- پرداخت قبوض
- دریافت موجودی حساب و ه‌ا گردش آخر
- انتقال کارت به کارت (شتابی و غیر شتابی)
- خرید شارژ
- شارژ کارت‌های مترو و اتوبوس شهری
- امکان احراز هویت (از طریق کارت ملی و اثر انگشت)



خودپرداز غیر نقدی مدل IAC PRIME-516K محصول شرکت ایران ارغام

- قابل نصب بر روی پایه و دیوار
- صفحه نمایش لمسی LCD 23.5"
- کارت خوان
- کارت مغناطیسی (Swipe Card Reader)
- کارت غیر تماسی (Contactless Card Reader)
- کارت مجهز به تراشه (Integrated Chip Card Reader)
- بارکد خوان 1D/2D
- صفحه کلید
- چاپگر رسید حرارتی 58mm
- دوربین

IAC PRIME - 516K CASHLESS

Motherboard	Processor	Intel J1900 Quad Core, 4G Ram, 128G SSD
	Network support	RJ-45 LAN interface and LED indicator
23.5 "Touch Screen LCD Screen	Model	23.5-inch capacitive touch screen
	Interface form	USB2.0
	Response time	less than 10 milliseconds
	Resolution	1920 x 1080
	Backlight	WLED
	Interface	EDP
EPP Pinpad	EPP pinpad	DES/3DES, PCI-6(Optional)
Magnetic Card Reade (Swipe)	Magnetic strip standard	ISO7810/7811
	Operation mode	Support 1/2/3 track reading
Contact IC Card Module	IC card standard	ISO7816 type 5V 5B type 3V card and support SLE4428, SLE4442, AT88SC1604 type memory card
	Card reading and writing speed	9600-96700bps
Contactless Card Reader	Support card type	Comply with ISO14443 Type A & B type CPU card, S50, S70 card
	Working frequency	13.56MHz ± 7kHz
	Communication parameters	1200/2400/4800/9600BPS optional
	Read and write speed	106Kbps
	Contact IC card communication distance	0-30MM
Thermal Receipt Printer	Printing method	Line thermal
	Print speed	75mm/sec
	Print paper width	57.5 ± 0.5mm
	Limited printing width	58mm
Password Keypad	Paper processing method	Automatic paper cutting (full or half cut)
	Key configuration	10 numeric keys. 6 function keys
	Function support	PIN encryption, MAC operation, data encryption and decryption. remote key management, PCI(Optional)
Temperature Measurement	Algorithm support	DES. Triple DES, RSA, SM2, SM3, SM4
		Support high and low temperature warning of human body, error ± 0.2 °C above 1 meter, can support thermal imaging
Power	Voltage	110-264V
	Working environment	-20-60°C, 20-90% RH
Camera	Face Camera	Support Automatic Infrared light compensation, visible light
Fingerprint	Support	
GSM Sim Card	Support	
Barcode Reader	1D/2D	1D/2D Barcode Reader